

Zip HydroTap® G4 BC

Boiling | **Chilled** | **Filtered** | **Instantly**



New under-bench Zip G4 Command-Centre™ leads the world in energy-saving technology, has a pin-code protected touch-screen to simplify adjustments, and automatically monitors performance to give an operating history if ever needed.



Boiling and chilled filtered water instantly, at a fraction of the cost of bottled water.

1. Saving energy.

- Superior Zip G4 thermal insulation now significantly reduces standard heat loss.
- Power-Pulse™ technology maintains boiling water to within 0.2°C of set temperature.
- Choice of 5 pre-set chilled water ranges.
- Boiling temperature can be pre-set: from 100°C down to 68°C.
- Sleeps or “powers-off” after two hours of non-use, to minimize daily power consumption.
- Automatically sleeps when the kitchen goes dark for added power savings overnight.
- Inbuilt 24/7 automatic timer turns power on and off over weekends or weekday periods.

2. User safety.

- Choice of fingertip control for fast cup filling (lever down) or hands-free pot filling (lever up).
- Can be set to finger-thumb operation to access boiling water, eliminating risk of accidental use.
- Can also be set to boiling water “isolation mode” for total safety when kitchen is unattended.

3. Healthier drinking.

- Inbuilt Zip 0.2 micron NSF-certified filter puts crystal-clear better-tasting water on tap, filtering out chlorine taste and odour and impurities as tiny as one five-thousandth of a millimetre, including protozoan cysts such as Cryptosporidium.
- Also reduces accumulation of mineral scale in boiling water appliances, but does not remove fluoride.
- Free-Flow™ bottle filling: for a continuing supply of filtered water even when chilling capacity is exceeded. (Chilled only).

Typical Specification

Under-bench boiling and chilled water appliance equipped with electronic tap head incorporating two way lever action control. Integral 500kPa pressure limiting and Dual Check valve, NSF certified 0.2 micron filter, air cooled refrigeration system with cleanable lint filter. Full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including a sensor activated “sleep when its dark” feature. Upgradable boiling water capacity with additional “Booster” module and the ability to adapt to provide approx. 55°C hot water for washing up to a secondary outlet with additional “Vented Mixer” kit.

Zip HydroTap® G4 BC

Boiling | Chilled | Filtered | Instantly

Order Code	Zip Model	Rating (kW) @ 230 V	Cabinet Dimensions W x D x H (mm)
HT1784	Zip HydroTap G4 BC	1.55	280 x 455 x 333

Order code shown here is for the model installed at a sink. To install on a "font" also specify a font kit: order code 90915.

A. Location

Tap must be positioned so that it drains into a suitable sink, or be installed on the optional tap "font kit" which is plumbed to waste. Tap should be situated as closely as possible to directly above the under-sink G4 Command-Centre. Maximum distance from the base of the tap to the G4 Command-Centre is one metre (may be extended if required). G4 Command-Centre must have clearances as shown on the drawings. Ventilation accessories (supplied) must be installed as per instructions.

B. Plumbing

Must be installed in accordance with AS/NZS3500 plumbing regulations. Designed for direct connection to a potable (drinkable) cold water supply with minimum pressure of 172 kPa. A 500 kPa pressure limiting valve and dual check valve are fitted internally to comply with AS/NZS3500. An isolating valve should be fixed between the water supply and the under-bench G4 Command-Centre.

C. Electrical

Designed to be connected to a 10 amp GPO, 240-230 volt AC power supply in accordance with AS/NZS3000 wiring regulations.

Caution

In some hard water areas where mineral scale accumulation can become a problem, consideration should be given to the maintenance required. All G4 Command-Centre units come with an internal bypass to simplify the connection of an added external filtration or water softening system.

Warranty



Five year warranty. Appliance warranty 36 months plus additional 24 months tank warranty. See website for details.

Accessories

- 90915 – Zip font installation kit
- 91290 – Zip 0.2 micron replacement filter

Standard tap finish: bright chrome. Brushed chrome or black also available.

Kits for increasing boiling water capacity of this installed G4 model or its conversion to All-In-One or Four-In-One can be supplied.

Call Zip for details and a quotation.

Accessibility

To order any model to be supplied with extension levers and Braille pads, add D to the end of the order code.

Technical Assistance

Zip Heaters (Aust) Pty Ltd
67-77 Allingham Street
Condell Park NSW 2200
Free Call 1800 638 622
www.zipindustries.com

As Zip policy is one of continuous product improvement, changes to specifications may be made without prior notice. The terms 'Zip', 'HydroTap', 'Power-Pulse', 'Free-Flow' and 'G4 Command-Centre' are trade marks.

